

Page 1

DATE OF PREPARATION:

4-24-86

EMERGENCY PHONE NO: (818) 579-6270

PRODUCT FORMULA: 3-1H-3

PRODUCT NAME: URETHANE HARDENER

PRODUCT CHEMICAL FAMILY: ALIPHATIC POLYISOCYANATE

[illegible]

BOILING POINT: 258.8°F

VAPOR DENSITY (AIR = 1): HEAVIER

SOLUBILITY IN WATER: NEGLIGIBLE

VAPOR PRESSURE: @20°C 8.0 mm.Hg.

SPECIFIC GRAVITY: 1.06

% VOLATILE BY VOLUME: 30%

EVAPORATION RATE: FASTER
(BUTYL ACETATE = 1)

FLASH POINT: 91 °F. TCC LEL: 1.0 % by Volume UEL: 7.6 % By Volume

EXTINGUISHING MEDIA: Foam, Dry Chemical, CO₂ and/or Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS:

During a fire, irritating and toxic gases and smoke are present from decomposition. Isolate from heat, sparks and open flames. Closed containers may burst when exposed to extreme heat. Vapors form an explosive mixture in air between the upper and lower explosive limits.

SPECIAL FIREFIGHTING PROCEDURES: Full emergency equipment with self-contained breathing apparatus should be worn by firefighters.